

CLAIMS

1. (Currently amended) A system for sharing power in a computer peripheral device, comprising:

a power supply interface adapted to receive an external bus power source;

a local power supply ~~comprising a circuit to be coupled to an external supply other than the external bus power source;~~ and

a power sharing circuit coupled to the local power supply and to the power supply interface, the power sharing circuit structured to ~~simultaneously~~ selectively provide power to the peripheral device from ~~both the local power supply and~~ or from the external bus power source or from both simultaneously; and

a load draw selection module to request additional power from the external bus power source if the power requirements of the peripheral device exceeds a set power threshold.

2. (Currently amended) The system according to claim 1, wherein when an amount of power required by the peripheral device is below a the set power threshold, the power sharing circuit is structured to provide power to the peripheral device from either the local power supply or from the external bus power supply.

3. (Currently amended) The system according to claim 2, wherein the power sharing circuit is structured to provide power to the peripheral device from the external bus power supply when the amount of power required by the peripheral device is below the set power threshold.

4. (Currently amended) The system according to claim 2 wherein the set power threshold is ~~100 mA~~ nominally 500mW.

5. (Currently amended) A system for sharing power in a computer peripheral device, comprising:

a local power supply;

a power supply interface adapted to receive an external power source; ~~and~~

a power sharing circuit coupled to the local power supply and to the power supply interface, the power sharing circuit structured to ~~simultaneously~~ selectively provide power to

the peripheral device from ~~both~~ the local power supply ~~and~~ or from the external power source or from both simultaneously; and

~~wherein the power sharing circuit comprises:~~

~~a resistive device coupled in series between the power supply interface and a load; and~~

~~a zener diode coupled to the resistive device~~

a suspend circuit to disconnect the computer peripheral device from the external power source responsive to a signal from the external power source.

6. (Canceled)

7. (Canceled)

8. (Canceled)

9. (Previously presented) The system according to claim 1, wherein the external bus power source is a computer bus.

10. (Original) The system according to claim 9, wherein the computer bus is a Universal Serial Bus.

11. (Previously presented) The system according to claim 1 wherein the local power supply comprises a transformer.

12. (Currently amended) A peripheral device comprising:
a load circuit for consuming power in the peripheral device;
a power source interface adapted to receive an external bus power source;
~~a local power source for providing power in the peripheral device from an external supply other than the external bus power source; and~~
a power sharing circuit coupled to the local power supply and to the power supply interface, the power sharing circuit structured to selectively provide power to the load circuit from ~~both~~ the local power source ~~and~~ or from the external bus power source ~~at the same time.~~ or from both simultaneously; and

a load draw selection module to request additional power from the external bus power source if the power requirements of the peripheral device exceeds a set power threshold.

13. (Currently amended) The device according to claim 12, wherein when an amount of power required by the load circuit is below a the set power threshold, the power sharing circuit is structured to provide power to the peripheral device from either the local power source or from the external bus power source.

14. (Currently amended) The device according to claim 12, wherein when an amount of power required by the load circuit is below a the set power threshold, the power sharing circuit is structured to provide power to the peripheral device from the external bus power source.

15. (Previously presented) The device according to claim 12, wherein when an amount of power required by the load circuit is above a first power threshold, but below a second power threshold, the power sharing circuit is structured to provide power to the peripheral device from either the external bus power supply, or from a combination of the external bus power supply and the local power supply.

16. (Currently amended) A peripheral device comprising:
a load circuit for consuming power in the peripheral device;
a local power source for providing power in the peripheral device;
a power source interface adapted to receive an external power source; and
a power sharing circuit coupled to the local power supply and to the power supply interface, the power sharing circuit structured to selectively provide power to the load circuit from ~~both~~ the local power source ~~and~~ or from the external power source ~~at the same time or from both simultaneously; and~~

~~wherein the power sharing circuit comprises:~~

~~a resistive device coupled in series between the power supply interface and the load circuit; and~~

~~a zener diode coupled to the resistive device and configured as a shunt regulator~~

a suspend circuit to disconnect the peripheral device from the external power source responsive to a signal from the external power source.

17. ~~(Canceled) The device according to claim 12, A peripheral device comprising:~~
~~a load circuit for consuming power in the peripheral device;~~
~~a local power source for providing power in the peripheral device;~~
~~a power source interface adapted to receive an external power source; and~~
~~a power sharing circuit coupled to the local power supply and to the power supply~~
~~interface, the power sharing circuit structured to provide power to the load circuit from both~~
~~the local power source and from the external power source at the same time;~~
~~wherein the power sharing circuit comprises:~~
~~a voltage regulator coupled in series between the power supply interface and~~
~~the load circuit; and~~
~~a resistive device coupled in series between the voltage regulator and the load~~
~~circuit.~~

18. (Previously presented) The device according to claim 12, wherein the external bus power source is a computer bus and is coupled to the power sharing circuit via a bus cable.

19. (Previously presented) The device according to claim 18, wherein the computer bus is a Universal Serial Bus.

20. (Currently amended) A method for providing power to a load circuit in a computer peripheral device, comprising:
providing from a bus power source external to the peripheral device power requirements of the load circuit up to a threshold amount of power; and
providing from a combination of the external bus power source and from an external power source other than the external bus power source the power requirements of the load circuit if the power requirements of the load circuit exceed the threshold amount; and
a load draw selection module to request additional power from the external bus power source if the power requirements of the peripheral device exceeds a set power threshold.

21. (Previously presented) The method of claim 20, wherein providing power requirements from the external bus power source comprises providing power from a computer bus.

22. (Original) The method of claim 21 wherein providing power requirements from a computer bus comprises providing power from a Universal Serial Bus.

23. (Previously presented) A method for providing power to a load circuit in a computer peripheral device, comprising:

providing from a power source external to the peripheral device power requirements of the load circuit up to a threshold amount of power;

providing from a combination of the external power source and from a power source internal to the peripheral device the power requirements of the load circuit if the power requirements of the load circuit exceed the threshold amount; and

requesting the external power source to provide all the power requirements of the load circuit above the threshold amount.

24. (Original) The method of claim 23, wherein requesting the external power source to provide all the power requirements of the load circuit comprises sending a signal to a bus power manager.

25. (Currently amended) A method for providing power to a load circuit in a computer peripheral device, comprising:

providing an initial amount of power to the load circuit from an external bus source;

allowing the load circuit to increase the amount of power drawn from the external bus source;

monitoring the amount of power drawn from the external bus source; and

adding power from a local external power source to the amount of power drawn from the external bus source once the amount of power drawn from the external bus source exceeds a threshold level; and

requesting the external bus source to provide all the power requirements of the load circuit above the threshold level.

26. (Previously presented) The method of claim 25, wherein providing power from an external bus source comprises providing power from a computer bus.

27. (Original) The method of claim 26 wherein providing power from a computer bus comprises coupling the peripheral device to a Universal Serial Bus.

28. (Previously Presented) A method for providing power to a load circuit in a computer peripheral device, comprising:

providing an initial amount of power to the load circuit from an external source;

allowing the load circuit to increase the amount of power drawn from the external source;

monitoring the amount of power drawn from the external source;

adding power from a local power source to the amount of power drawn from the external source once the amount of power drawn from the external source exceeds a threshold level; and

requesting the external source to provide all the power used by the load circuit if the amount of power drawn from the external source exceeds the threshold level.

29. (Previously Presented) The device according to claim 12, wherein the local power supply comprises a transformer.